



Used as strippers, pressure cylinders in bulging applications as tube bending mandrels & for machining variety of parts

Rods

Standard Lengths are: 6", 12", 24", 36" and 48"

Hardnesses: 20A, 30A, 40A, 60A, 70A, 80A, 90A, 95A, and 75D

Standard Colors: Amber or Black (Other Colors Available)

When ordering RODS with a +Tolerance YOU MUST REQUEST the +Tolerance on your purchase order, because those rods are also available in the +/-2% sizes

Diameter	Tolerance	Diameter	Tolerance
1/4 "	+ 0.025 " / -0"	1-1/2 "	+ 0.050 " / -0"
3/8 "	+ 0.025 " / -0"	1-5/8 "	+/- 2 %
1/2 "	+ 0.025 " / -0"	1-3/4 "	+ 0.050 " / -0"
5/8 "	+ 0.025 " / -0"	2 "	+ 0.050 " / -0"
3/4 "	+ 0.025 " / -0"	2-1/4 "	+ 0.050 " / -0"
7/8 "	+ 0.025 " / -0"	2-1/2 "	+ 0.050 " / -0"
1 "	+ 0.025 " / -0"	3 "	+ 0.050 " / -0"
1-1/8 "	+ 0.050 " / -0"	3-1/2 "	+/- 2 %
1-1/4 "	+ 0.050 " / -0"	4 "	+/- 2 %
1-3/8 "	+/- 2 %	5*	+/- 2 %